HIGH EFFICIENCY PICTURE CODER

Patent number:

JP3001688

Publication date:

1991-01-08

Inventor:

KAMIKURA KAZUTO; SAWADA KATSUTOSHI

Applicant:

NIPPON TELEGRAPH & TELEPHONE

Classification:

- international:

H04N7/13

- european:

Application number:

JP19890135370 19890529


Priority number(s):

JP19890135370 19890529

Report a data error here

Abstract of JP3001688

PURPOSE: To improve the coding efficiency and the reduction picture quality in the case of reproduction of a reduced picture by providing a macro block processing means, and interfield block processing means, an in-field block processing means and a block selection means. CONSTITUTION:A picture signal subject to 2:1 interlace scanning is inputted from an input terminal 1 and a macro block processing circuit 2 splits the signal into plural macro blocks each comprising 8-picture element X 16-line. Then a moving still deciding circuit 3 decides whether or not a video image in each macro block is moved or at standstill and when it is decided that the picture is at standstill, switches 4, 7 are connected to an inter-field block processing circuit 5. When it is decided that the picture is moving, the switches 4, 7 are connected to in-field block processing circuit 6. Thus, the forming method of the block is switched adoptively in the unit of macro blocks to improve the coding efficiency and when a reduced picture is reproduced, the quality of the reduced picture is improved.



Data supplied from the esp@cenet database - Worldwide